

For even greater productivity, consider mounting the Ultimus V dispenser on an EFD benchtop robot

Features

- Auto Increment mode adjusts dispensing parameters after a certain number of shots or a specific lapsed time
- 400 individual memory storage cells
- Steady, Timed and Teach modes
- Multi-level operator lockout
- End of Cycle Feedback loop
- External PC interface for data input
- Display cycle counter
- RS-232 interface compatible with the Musashi 808FX
- D-sub I/O (15-pin) and Communication (9-pin) connections
- Alarm I/O signals



Specifically designed to work with the Ultimus V, the patent-pending Optimeter™ provides even greater control when dispensing all fluids by automatically increasing airflow as the syringe barrel empties.



Greater positioning accuracy - puts fluid deposits in the same place every time

Much faster than manual application

Allows parts to be processed in batches vs one at a time

Frees operators to perform more value-added tasks

Easy to move to different locations as needed



For EFD sales and service in over 30 countries, contact EFD or go to www.efd-inc.com

EFD, Inc.

East Providence, RI USA

USA & Canada: 800-556-3484; +1-401-431-7000

info@efd-inc.com

www.efd-inc.com

EFD International Inc.

Dunstable, Bedfordshire, UK

0800 585733 or +44 (0) 1582 666334

Ireland 00800 8272 9444

europe@efd-inc.com

www.efd-inc.com

EFD, Inc., Asia

China: +86 (21) 3866 9006

china@efd-inc.com

www.efd-inc.com

Singapore: +65 6796 9522

sin-mal@efd-inc.com

The Wave Design is a trademark of Nordson Corporation. Optimeter patent pending.
©2009 Nordson Corporation v081909